

Portable Nitrogen Pressure Sources

Self-contained pressure source lets you calibrate both high- and low-pressure systems in most remote locations

Fully integrated Nitropak pressure source has an onboard nitrogen cylinder, volume controller with two outlet ports, and pressure regulator—all contained in a rugged carrying case. Cylinder has a 15.2 cubic foot volume and lasts 1 to 2 days—making it ideal for use in plants, pipelines, ships and offshore applications. The cylinder is marked for use in US or Canada; can be easily refilled in a shop.

- Easy-to-refill nitrogen cylinder holds enough gas for multiple calibrations
- Proprietary pressure-balanced, fine-adjustment piston
- Extremely precise, fingertip control of pressure at 0.03 psi (2 mbar) or 3000 psi (210 bar) or any range in between
- Quickly attach hose, gauge adapter and process connection without thread sealant or a wrench
- Nylon bag holds hose and fittings and is conveniently attached to inside of lid
- Storage compartment in control panel for pressure reference test gauge



68987-71

SPECIFICATIONS

Pressure range	0 to 3000 psi (0 to 207 bar)
Vacuum range	0 to 10 in. Hg (0 to 254 mm Hg)
Pressure media	Compressed gas, air
Fine adjust resolution	±0.001 psi
Operating temperature	0 to 130° F (–18 to 54° C)
Construction	Anodized aluminum, brass, stainless steel, ABS plastic
Seal materials	Buna N, Delrin® acetal, PTFE
Cylinder capacity	15.3 cu. ft. (425 L)
Dimensions (W x H x D)	14 ¹ / ₁₆ " x 18 ¹ / ₂ " x 7 ¹ / ₂ " (370 x 470 x 190 mm)

What's included: Quick-test System™ outlet connections, Quick-test™ low-volume hoses with brass hose ends and hose adapters (as indicated in table), and carrying case.

Catalog No.	Model No.	Gauge adapter included	Gauge included	Hoses included (2)	Hose adapters included (2)	
TS-68987-71	NPAK-0000-0-0	—	—	—	—	
TS-68987-72	NPAK-1MBA-6-3	1/8" NPT(M)	—	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
TS-68987-73	NPAK-2MBA-6-3	1/4" NPT(M)	—	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
TS-68987-74	NPAK-2FBA-6-3	1/4" NPT(F)	—	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
TS-68987-75	NPAK-1KPSIG-M	1/4" NPT(F)	Analog, 1000 psi, ±0.25% FS	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
TS-68987-76	NPAK-1KPSIG-D	1/4" NPT(F)	Digital, 1000 psi, ±0.25% FS	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
TS-68987-77	NPAK-3KPSIG-M	1/4" NPT(F)	Analog, 3000 psi, ±0.25% FS	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
TS-68987-78	NPAK-3KPSIG-D	1/4" NPT(F)	Digital, 3000 psi, ±0.25% FS	3 ft (0.9 m), 6 ft (1.8 m)	1/4" NPT(M), brass	
Accessories						
TS-17012-15	—	NIST-traceable calibration with data				

Get the **BE\$T** Pricing!

Call us 0984 843 683

E-mail us sales@ttech.vn

Go to store.ttech.vn